



VALUX iluminación S.L C/ ALGEPERS, 24-8 PARQUE EMP. TACTICA 46980 PATERNA (Valencia) Spain

CERTIFICADO DE CONFORMIDAD N° LUM0853469-CE
CERTIFICATE OF COMPLIANCE Nr. LUM0853469-CE

Datos del producto conforme a normas / Data of the product according to norms

Modelos/Model: Pastev

Codigo / Code :VXCH96949

Descripción funcional/Functional description: Luminaria fija de uso general/Luminaire for General Lighting. LED10W E27 Class II IP20 / Fix general purpose luminaire. LED10W E27 Class II IP20.

This is to certify and confirm that this product is manufactured and tested in full compliance with the latest EU norms and regulations as listed in the flowing table:

Directiva aplicada y Normas utilizadas/Directives applied and standards used

2014/35/EU LOW VOLTAGE DIRECTIVE

LOW VOLTAGE DIRECTIVE

2014/30/EU ELECTROMAGNETIC COMPATIBILITY
DIRECTIVE

ELECTROMAGNETIC COMPATIBILITY DIRECTIVE

2011/65/EU ROHS DIRECTIVE 2009/125/EU ERP
DIRECTIVE, ENERGY RELATED PRODUCTS

ROHS DIRECTIVE

ERP DIRECTIVE, ENERGY RELATED PRODUCTS

REGULATION CE 245/2009 + UE 347/2010 REGULATION
UE 1428/2015

REGULATION CE 245/2009 + UE 347/2010

REGULATION UE 1428/2015

The following harmonised standards and technical
specifications have been applied:

EN 61547:2009 EN 60598-1:2015

EN 61000-3-2:2014 EN 62493:2010

EN 61000-3-3:2013 EN

60598-2-22:1998+A1:2003+A2:2008

EN 55015:2013 EN 60598-2-2:2012

Fecha de emisión/Emission date: 12/05/2021



Manufacturing Quality Standard:

• ISO 9001:2008

LED Luminaire Standard:

• ENIEC 60598-1 • IEC 62560
• ENIEC 60598-2-1 • ENIEC 60061-1
• ENIEC 60598-2-2 • EN 13032-1
• ENIEC 90529 • EN 13032-2
• ENIEC 32477-2 • ENIEC 62471
• IEC 62612 • ENIEC 60825
• ENIEC 60968 • EN 60061-1

Electronic Driver Standard:

• ENIEC 61347-1 • ENIEC 31000-3-3
• ENIEC 61347-2-13 • ENIEC 31547
• ENIEC 62384 • EN 55015(CISPR 15)
• ENIEC 61000-3-2

LED Module Standard:

• IEC 62031

• IEC 60685-2-2

LED Light Photometric Standard:

• CIE: TM14; LM-75; IES; LDT; CEN; CIB

RoHS Standard:

• EPA3050B • EPA7196A
• EN 1122B • EPA3540C
• IEC 62321 • EPA8270D
• EPA3052
• EPA3060A

LED Luminaire Performance:

• LM-R0-C0
• Switching cycle:100 000x